Contribution ID: 10

Type: not specified

Growth systems for microalgae biomass production

Cultivating of microalgae has led to increasing commercial interest in their use for producing valuable substances for food, feed, cosmetics, pharmaceuticals, and biodiesel et al., as well as for mitigation of environmental pollution and CO2 emissions. Some technical barriers exist on the commercialization of microalgal biomass and products thereof. These are mostly related to the cultivation of large quantities of microalgae biomass to meet energy demands, which is limited by the light-to-biomass conversion efficiency and harvesting systems as well.

Microalgae growth strongly requires light energy and CO2 for photosynthetic production of biomass. Hence the design and use of effective cultivation system that allows light penetration and an efficient supply of CO2 is an important requirement for the rapid cultivation of microalgae and their further commercial use. Microalgae can be cultivated generally in two different aquaculture systems, namely open pond and closed photobioreactors (PBR). The open ponds are the simplest systems, while closed (PBR) could be in form of plates or tubes. Microalgae receive sunlight directly through the transparent container walls or through light fibers or tubes that channel it from light collectors.

As compared with open-air systems, there are distinct advantages to using closed systems, but technical challenges remain. Enclosed systems are advantageous for algae which are prone to contamination while open systems are suitable for robust microalgae, which can resist high pH or salinity when cultivated e.g. in marine water. For most of these cultivation methods, the production processes are economically viable and technical improvements are still in progress. Recently there have been various approaches for cultivation and biomass harvesting developed. However, for effective and sustainable microalgae biomass production further development of more controllable, cost-efficient systems and manufacturing devices is required to maximize productivity, especially for large scale industrial use.

This study was performed within the EMFF funded project no. 20-00-F02201-000001 "Approbation of microalgae cultivation in closed aquaculture systems and evaluation of their efficiency in fish feed" supported by the Ministry of Agriculture and Rural Support Service of the Republic of Latvia.

Primary authors: KRECERS, Kārlis (Laboratory of Industrial Microbiology and Food Biotechnology, Institute of Biology, University of Latvia, Ojara Vaciesa street 4, Riga, LV-1004, Latvia); Dr SEMJONOVS, Pāvels (Laboratory of Industrial Microbiology and Food Biotechnology, Institute of Biology, University of Latvia, Ojara Vaciesa street 4, Riga, LV-1004, Latvia);

Presenter: KRECERS, Kārlis (Laboratory of Industrial Microbiology and Food Biotechnology, Institute of Biology, University of Latvia, Ojara Vaciesa street 4, Riga, LV-1004, Latvia)